


FIG. 22R

Beam Clamp Retaining Strap

LOCAL: 860 647 1431 • TOLL FREE: 800 243 4844 • ORDERS@EMPIREINDUSTRIES.COM • QUOTES@EMPIREINDUSTRIES.COM



Domestically Manufactured

Materials/Finishes	Pre-Galvanized (22RG)		
	T-304 Stainless Steel: 3/8" - 1/2", 13ga x 1" (22RSS)		
	T-316 Stainless Steel: 3/8" - 1/2", 13ga x 1" (22RSX)		
Variants:	N/A		
Service:	Designed for use with FIG. 61 and FIG. 62.		
Approvals:	N/A		
Ordering:	Specify figure number, finish and length		
Notes:	Add 2" minimum to flange width to determine length. Custom lengths available.		

ROD SIZE	MATERIAL	WGT EACH (lbs)					
Α		LENGTH L					
		4-1/2	6	8	10	12	14
3/8	14ga x 1	.14	.18	.26	.32	.40	.46
1/2	14ga x 1	.14	.18	.26	.32	.38	.44
5/8	14ga x 1-3/16	.17	.22	.30	.40	.47	.55
3/4	14ga x 1-3/16	.17	.22	.30	.40	.47	.55
7/8	14ga x 2	.28	.36	.48	.64	.76	.88

PROJECT INFORMATION	APPROVAL STAMP
Project:	APPROVED AS NOTED
Address:	NOTES:
Contractor:	
Engineer:	
Date:	
APPROVED	
NOT APPROVED	

