



| | | |
|--------------------|---|--------------------------|
| Materials/Finishes | Plain Ductile Iron (61B) | Electro-Galvanized (61G) |
| | T-316 Stainless Steel (61SX) | |
| Service: | Designed to attach hanger rod to the top or bottom flange of a beam or bar. | |
| Approvals: | Complies with Federal Specification A-A-1192A (Type# 19) and Manufacturers' Standardization Society MSS SP-58 and SP-69 (Type# 19). | |
| Ordering: | Specify figure number, finish and rod size | |
| Notes: | See MSS SP-69 for proper set screw torque recommendations. | |

| ROD SIZE A | SET SCREW | B | C | D | E | F | MAX PIPE SIZE | WGT EACH (lbs) | MAX REC LOAD (lbs) STANDARD |
|---------------|--------------|-------|-------|-----|-------|-------|------------------|-------------------|-----------------------------------|
| 5/8-11 | 3/8-16 | 1-7/8 | 2-3/8 | 5/8 | 1-3/8 | 1-1/4 | 5 | 0.66 | 1130 |
| 3/4-10 | 3/8-16 | 1-7/8 | 2-3/8 | 5/8 | 1-3/8 | 1-1/4 | 6 | 0.83 | 1130 |

| PROJECT INFORMATION | | | APPROVAL STAMP | |
|---------------------|-------------------|--------------|----------------|--|
| Project: | | | Notes: | |
| Address: | | | | |
| Contractor: | | | | |
| Engineer: | | | | |
| Date: | | | | |
| Approved | Approved as Noted | Not Approved | | |