



"E" Dimension includes exposed rod threads beyond bottom of hex nut. Exposed rod thread dimension is equal to the diameter of the rod used.



Materials/Finishes	Plain Carbon Steel (11VB)	Electro-Galvanized (11VG)
	Hot-Dip Galvanized (11VHDG)	T-304 Stainless (11VSS)
	T-316 Stainless (11VSX)	
Service:	Designed for the suspension of flexible plastic pipe lines. Used in conjunction with figure #12 channel.	
Ordering:	Specify figure number, finish and pipe size	
Notes:	Hanger and channel sold separately. Upper locknut must be tightened securely to assure proper hanger performance.	

PIPE SIZE	SIZE NO.	BOLT	A	B	C	D	E	F	WGT EACH (LBS)	MAX REC LOAD (LBS)
1/2	1	1/4	3/8	5-3/16	5-7/8	2-9/16	4-7/16	1-1/4	.30	250
3/4	1	1/4	3/8	5	5-7/8	2-9/16	4-1/4	1-1/4	.30	250
1	1	1/4	3/8	4-7/8	5-7/8	2-9/16	4-1/16	1-1/4	.30	250
1-1/4	1	1/4	3/8	4-5/8	5-7/8	2-9/16	3-7/8	1-1/4	.30	250
1-1/2	1	1/4	3/8	4-7/16	5-7/8	2-9/16	3-11/16	1-1/4	.30	250
2	1	1/4	3/8	4-1/8	5-7/8	2-9/16	3-3/8	1-1/4	.30	250
2-1/2	2	3/8	1/2	6-13/16	8-15/16	4-11/16	5-3/4	2-3/8	.96	300
3	2	3/8	1/2	6-3/8	8-15/16	4-11/16	5-5/16	2-3/8	.96	300
4	2	3/8	1/2	5-11/16	8-15/16	4-11/16	4-1/2	2-3/8	.96	300
5	3	1/2	3/4	7-3/4	11-3/4	6-7/8	6-1/2	1-3/4	3.05	350
6	3	1/2	3/4	6-13/16	11-3/4	6-7/8	5-3/16	1-3/4	3.05	350
7	4	5/8	3/4	8-13/16	14-1/2	9-1/4	7-9/16	1-7/8	4.65	400
8	4	5/8	3/4	6-5/16	14-1/2	9-1/4	7-1/16	1-7/8	4.65	400
10	5	3/4	7/8	10-5/8	18-3/8	11-1/4	9-1/8	2-1/4	9.05	550

PROJECT INFORMATION	APPROVAL STAMP
Project:	APPROVED AS NOTED
Address:	NOTES:
Contractor:	
Engineer:	
Date:	
APPROVED	
NOT APPROVED	