



| | | |
|----------------------------|---|---------------------------------------|
| Materials/Finishes: | Plain Carbon Steel, Imported (13BI) | Hot-Dip Galvanized, Imported (13HDGI) |
| | T-304 Stainless, Imported (13SSI) | T-316 Stainless (13SX) |
| Variants: | Domestic | Oversized Tap |
| | Special Thread Direction | |
| Service: | Designed for use on high temperature piping applications. | |
| Approvals: | Complies with Federal Specifications WW-H-171-E (Type# 17), A-A-1192 A (Type# 17), and Manufacturers' Standardization Society MSS SP-58 (Type# 17). | |
| Ordering: | Specify figure number, finish and rod size. | |
| Notes: | Supports loads equal to the full limitation of the hanger rod. When figure 13 is supplied in hot-dip galvanized finish, it is not tapped oversized. | |

| 13BI AND 13HDGI | | | | | | | | | |
|-----------------|-------|-------|-----|-------|--------|-------|----------------------|--------------------|-------|
| SIZE A | B | C | D | E | F | G | WGT EACH (lbs) | MAX REC LOAD (lbs) | |
| | | | | | | | | 650°F | 750°F |
| 3/8-16 | 1-1/4 | 13/16 | 3/8 | 1-3/8 | 15/16 | 5/8 | 0.23 | 730 | 540 |
| 1/2-13 | 1-1/4 | 13/16 | 3/8 | 1-3/8 | 15/16 | 5/8 | 0.55 | 1350 | 1010 |
| 5/8-11 | 1-1/2 | 1-1/4 | 1/2 | 2 | 1-7/16 | 11/16 | 0.52 | 2160 | 1610 |
| 3/4-10 | 1-1/2 | 1-1/4 | 1/2 | 2 | 1-7/16 | 11/16 | 1.70 | 3230 | 2420 |
| 7/8-9 | 2 | 1-3/4 | 3/4 | 2-3/8 | 2 | 1 | 1.70 | 4480 | 3360 |
| 1-8 | 2 | 1-3/4 | 3/4 | 2-3/8 | 2 | 1 | 1.70 | 5900 | 4420 |
| 1-1/8-7 | 2-1/2 | 1-7/8 | 1 | 3-3/8 | 2-3/8 | 1-1/4 | 3.70 | 6230 | 5560 |
| 1-1/4-7 | 2-1/2 | 1-7/8 | 1 | 3-3/8 | 2-3/8 | 1-1/4 | 3.50 | 9500 | 7140 |
| 1-1/2-6 | 2-1/2 | 1-7/8 | 1 | 3-3/8 | 2-3/8 | 1-1/4 | 3.50 | 13800 | 10370 |

| PROJECT INFORMATION | APPROVAL STAMP |
|---------------------|-------------------|
| Project: | APPROVED AS NOTED |
| Address: | NOTES: |
| Contractor: | |
| Engineer: | |
| Date: | |
| APPROVED | |
| NOT APPROVED | |