



Materials/Finishes:	Painted Carbon Steel Housing with Neoprene Rubber Element (34)
Service:	Designed for effective vibration isolation for piping or suspended equipment. Typical applications include fans, air handling units, piping and suspended ceilings.
Ordering:	Specify figure number, isolator size, rod size and load.

ISOLATOR SIZE	MAX REC LOAD (lbs)	DEFLECTION	DIMENSIONS				
			A	B	C	D	E
EMP-1-A	60	0.50	4	2-7/8	2-1/2	1/2	1-7/8
EMP-1-B	130	0.50	4	2-7/8	2-1/2	1/2	1-7/8
EMP-1-C	250	0.50	4	2-7/8	2-1/2	1/2	1-7/8
EMP-1-D	430	0.50	4	2-7/8	2-1/2	1/2	1-7/8
EMP-2-A	380	0.50	5-1/2	3-3/4	4	3/4	2-3/8
EMP-2-B	520	0.50	5-1/2	3-3/4	4	3/4	2-3/8
EMP-2-C	840	0.50	5-1/2	3-3/4	4	3/4	2-3/8
EMP-2-D	1070	0.50	5-1/2	3-3/4	4	3/4	2-3/8
EMP-3-A	750	0.50	6-1/4	4-1/4	5-3/8	1	2-3/8
EMP-3-B	1350	0.50	6-1/4	4-1/4	5-3/8	1	2-3/8
EMP-3-C	1900	0.50	6-1/4	4-1/4	5-3/8	1	2-3/8
EMP-3-D	3050	0.50	6-1/4	4-1/4	5-3/8	1	2-3/8



PROJECT INFORMATION	APPROVAL STAMP
Project:	APPROVED AS NOTED
Address:	NOTES:
Contractor:	
Engineer:	
Date:	
APPROVED	
NOT APPROVED	