



Materials/Finishes:	Plain Malleable Iron (41HB)	Electro-Galvanized (41HG)
	Chrome Plated (41HCR)	
Service:	Designed for the suspension of non-insulated stationary pipe lines horizontally or vertically.	
Approvals:	Complies with Federal Specification WWH-171-E (Type# 25), A-A-1192A (Type# 12), Manufacturers' Standardization Society SP-58 and MSS SP-69 (Type# 12).	
Ordering:	Specify figure number, finish and pipe size	

PIPE SIZE	PIPE OD	SCREW	A	B	C	D	WGT EACH (LBS)	MAX REC LOAD (LBS)
3/8	0.675	10-24	3/8-16	11/16	1-13/16	1-3/16	0.084	180
1/2	0.840	10-24	3/8-16	3/4	2-1/8	1-3/16	0.098	180
3/4	1.050	10-24	3/8-16	7/8	2-1/2	1-9/16	0.112	180
1	1.315	10-24	3/8-16	1-1/8	2-3/4	2	0.147	180
1-1/4	1.660	10-24	3/8-16	1-5/16	3-3/16	2-3/8	0.181	180
1-1/2	1.900	10-24	3/8-16	1-7/16	3-3/8	2-5/8	0.214	180
2	2.375	10-24	3/8-16	1-5/8	3-15/16	3-1/16	0.299	180
2-1/2	2.875	1/4	1/2-13	2-1/8	5-3/16	3-13/16	0.583	300
3	3.500	1/4	1/2-13	2-1/2	5-11/16	4-5/8	0.713	300
4	4.500	1/4	1/2-13	2-7/8	6-3/4	5-9/16	1.019	300

PROJECT INFORMATION	APPROVAL STAMP
Project:	APPROVED AS NOTED
Address:	NOTES:
Contractor:	
Engineer:	
Date:	
APPROVED	
NOT APPROVED	